


TECHNICAL DATA SHEET

DOUBLE-SIDED TAPES



BN 30500

CARRIER	Polyethylene foam
LINER	Siliconized paper
COLOR	White
ADHESIVE	Natural rubber and resins
TOTAL THICKNESS	800 μm (AFERA 4006-ED.9/79)
ADHESION TO STEEL	650 cN/cm (AFERA 4001-ED.10/87)
TACK	1 cm (PSTC 6-ED. 86)

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

To fix house-hold, furnitures industry accessories and temporary panels placement. It can resist at 100°C for short periods and at temperatures lower than 70 °C for long periods. The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
Crosslinked natural rubber adhesive	Good ageing, solvent and water resistance Works at low temperatures
Foam carrier (67Kg/m ³ density)	High conformability
Single air-proof bag	Dust and humidity proof Long lasting product

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889

Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

