

TECHNICAL DATA SHEET

DOUBLE-SIDED TAPES



BN 30800

CARRIER	White polyethylene foam
LINER	Brown siliconized paper
COLOR	White
ADHESIVE	Acrylic
TOTAL THICKNESS	1000 μm (AFERA 4006-ED.9/79)
ADHESION TO STEEL	1000 cN/cm (AFERA 4001-ED.10/87)
HEAT RESISTANCE	100 °C (BT internal metod PS-QUA-14)

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

For all mounting and bonding applications.

It can resist at 100°C for short periods and at temperatures lower than 90 °C for long periods.

The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging.

The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
High quality adhesive	High adhesion
	High shear
Foam carrier (67Kg/m ³ density)	High conformability
Single air-proof bag	Dust and humidity proof
	Long lasting product

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889

Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

