

TECHNICAL DATA SHEET

REPULPABLE TAPES

CARRIER	Paper
LINER	White siliconized repulpable paper
COLOR	Light blue
ADHESIVE	Water soluble acrylic
TOTAL THICKNESS	60 μm (AFERA 4006-ED.9/79)
ADHESION TO STEEL	550 cN/cm (AFERA 4001-ED.10/87)
TACK	3 cm (PSTC 6-ED. 86)
HEAT RESISTANCE	200 °C (BT internal method PS-QUA-14)
REPULPABILITY	Full (TAPPI UM213-ED. 91)*

^{*}Non-rapresentative results can occur if test guidelines are not followed.

BN 6366

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

For permanent overlap splices at rereelers; for tissue, cigarette papers and very light uncoated papers.

The tape can be stored for maximum 10 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
Fully repulpable	No contamination and waste recycling
High cohesion adhesive	The splices do not slip under tension into the ovens
	No bleeding
Low thickness	More thin splices
Repulpable liner with "super easy" siliconizing	Stiff and easy peel
Single air-proof bag	Dust and humidity proof

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889 Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91







