

TECHNICAL DATA SHEET

HANDLE TAPES



BACKING	Polypropylene
COLOR	Clear
TYPE OF ADHESIVE	Hotmelt
TOTAL THICKNESS	72 μ m (AFERA 4006-ED.9/79)
ADHESION TO STEEL	400 cN/cm (AFERA 4001-ED.10/87)
MD TENSILE STRENGTH	15 daN/cm (AFERA 4004-ED.9/79)
MD ELONGATION AT BREAK	20 % (AFERA 4005-ED.9/79)
SPOOL DIMENSIONS	25mm x 5000m (most commonly used)
CORE DIMENSIONS	152 mm ϕ – 180 mm (width)

BN 6482 HM

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

Handling system for plastic or carton packages of mineral water bottles, beverages and tetra-brick, by application after film shrinkage.

The tape can be stored for maximum 6 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES	BENEFITS
Mono-oriented polypropylene backing	High tensile strength	It holds safely the package during transportation
Hotmelt adhesive	High adhesion to the package	It holds safely the package during transportation

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, held responsible for not proper use. Warranty is limited to replacement of products that Boston tapes proves to be defective and keeps out any other damages.

www.bostontapes.it - infos@bostontapes.it

BOSTON tapes S.p.A.

Sales and Marketing Office: via G.Sirtori 45, 20017 Passirana di Rho (MI) Italy. Phone: (+39) 02 937521 Fax: (+39) 02 9301605
Plant and Registered Office: Strada Provinciale Celiole - Piedimonte, 81037 Sessa Aurunca (CE) Italy. Phone: (+39) 0823 680211 Fax: (+39) 0823 703889
Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

**COMPANY
WITH QUALITY SYSTEM
CERTIFIED BY DNV
=ISO 9001/2000=**


a CHARGEURS company