

TECHNICAL DATA SHEET

STRAPPING TAPES



BACKING Mono-oriented Polypropylene

COLOR Orange

ADHESIVE Natural rubber and resins

TOTAL THICKNESS 70 μm (AFERA 4006-ED.9/79)

ADHESION TO STEEL 320 cN/cm (AFERA 4001-ED.10/87)

MD TENSILE STRENGTH 16 daN/cm (AFERA 4004-ED.9/79)

BN 6486

MD ELONGATION AT BREAK 25 % (AFERA 4005-ED.9/79)

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

For sealing, bundling, palletizing and storage of bulky and heavy packages. The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
Mono-oriented polypropylene backing	High tensile strength and low elongation
Single air-proof bag	Dust and humidity proof
	Long lasting product

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889

Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

