

TECHNICAL DATA SHEET

REPULPABLE TAPES



BN 7000

CARRIER	Cellulose fiber tissue
LINER	White siliconized repulpable paper
COLOR	Blue or yellow
ADHESIVE	Water soluble acrylic
TOTAL THICKNESS	100 μ m (AFERA 4006-ED.9/79)
ADHESION TO STEEL	700 cN/cm (AFERA 4001-ED.10/87)
TACK	2 cm (PSTC 6-ED. 86)
HEAT RESISTANCE	200 °C (BT internal method PS-QUA-14)
REPULPABILITY	Full (TAPPI UM213-ED. 91)*

*Non-representative results can occur if test guidelines are not followed.

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

For high speed flying splices on coaters.

The tape can be stored for maximum 8 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight.

Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
Fully repulpable	No contamination and waste recycling
High quality adhesive	Very good grasp during flying splices
Repulpable liner with "super easy" siliconizing	Stiff and easy peel
Single air-proof bag	Dust and humidity proof

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889

Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

