

TECHNICAL DATA SHEET

TECHNICAL TAPES



BN 98 FT

BACKING	Polyolefinic copolymer
COLOR	White
ADHESIVE	Synthetic rubber and resins
TOTAL THICKNESS	85 μ m (AFERA 4006-ED.9/79)
ADHESION TO STEEL	700 cN/cm (AFERA 4001-ED.10/87)
ADHESION TO BACKING	< 100 cN/cm (AFERA 4001-ED.10/87)
MD TENSILE STRENGTH	> 1 daN/cm (AFERA 4004-ED.9/79)
MD ELONGATION AT BREAK	> 350 % (AFERA 4005-ED.9/79)

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

For fixing and protecting refrigeration coils on freezers' walls, before polyurethane foam injection. Available also in spools. The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
Special release coated polyolefinic backing	High conformability
	Good polyurethane foam grasp
Synthetic rubber adhesive	High adhesion

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889

Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

