

# DuploCOLL® 377

Art. No. 11 00 73

## Double-sided, transparent, distortion-free adhesive mounting tape

### Product construction

	Name	Colour	Thickness [mm]
Liner	Polypropylene film	red	approx. 0,08
Adhesive covered side	Modified acrylic		
Carrier	Polyester film	transparent	approx. 0,20
Adhesive open side	Modified acrylic		
Total thickness:			approx. 0,28

### Product advantages

- Good initial and final adhesion
- High shear strength
- Good ageing resistance
- Extensive resistance to the influence of chemicals (domestic cleaning material and polishing agents)

### Main application fields

- Making plastics, signs, face plates and scales in the electrical and electronic industries self-adhesive
- Self-adhesive, distortion-free preparation of rubber goods (mouldings, profiles)

### Product features

### Applicability on

Initial adhesion	● ● ●	Foam	○ ○ ○
Final adhesion	● ● ○	Rubber	● ● ○
Dimensional stability	● ● ●	Fabric	● ● ●
Adhesion on even surfaces	● ● ●	Glass/Ceramics	● ● ●
Adhesion on rough surfaces	● ● ●	Wood	● ● ●
Ageing resistance	● ● ○	High energy plastics: PVC, PC, ABS,...	● ● ●
Weathering resistance	● ● ○	Low energy plastics: PE, PP,...	● ● ○
Chemical resistance	● ● ○	Metal	● ● ●
Resistance to plasticizers	● ● ●	Paper/Cardboard	● ● ●

● ● ● very suitable    ● ● ○ suitable    ● ○ ○ suitable with reductions    ○ ○ ○ not suitable

### Specific technical data\*

#### Temperature range

-40 °C to +120 °C

\* Specific test results, statistically not approved.


# DuploCOLL® 377

Art. No. 11 00 73

**Double-sided, transparent, distortion-free adhesive mounting tape**

## Technical Data

<b>Shear strength</b>	on steel according to DIN EN 1943, edition 1996, at +23 °C +/- 2 °C	60 N/625 mm <sup>2</sup>
<b>Peel strength</b>	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2 °C	35 N/25 mm



## Application

<b>Recommended application temperature</b>	18 °C to 35 °C
<b>Application guidelines</b>	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

## Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).  
The storage stability is one year after delivery.

## Product presentation

<b>Converted product</b>	Rolls				
<b>Width [mm]</b>	> 6	> 12			
<b>Length [m]</b>	50	100/200			
<b>Max. log width: 1260 mm</b>	Other dimensions, die-cuts and sheets on request.				

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

The physical characteristics contained in our data sheets represent typical or average values. They do not represent any warranties or guarantees and must not be used for technical specification purposes. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. The buyer is responsible for determining the suitability of the specific tape for its intended use in connection with user's method of application. Please consult our Technical Applications Department for specific advice. Our general Term and Conditions of Sale apply, particularly with regard to warranty and liability.

Date of issue: May 2011

Lohmann GmbH & Co. KG  
Irlicher Strasse 55  
56567 Neuwied  
Germany  
Phone: + 49 (0) 26 31 34 - 0  
Fax: + 49 (0) 26 31 34 - 6661  
E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further Information  
[www.lohmann-tapes.com](http://www.lohmann-tapes.com)

Concerning product safety (confirmation, conformity to guidelines, REACH, etc.) please use the following  
E-mail address: [products.safety@lohmann-tapes.com](mailto:products.safety@lohmann-tapes.com)

