

DuploFLEX® 3.4

Art. No. 11 02 79

Compressible 0,38 mm (0.015") thick adhesive tape with distinctive orange colour for the mounting of plates in high-quality flexographic printing

Product construction			
	Name	Colour	Thickness [mm]
Liner	embossed polyethylene film	white	approx. 0,14
Adhesive covered side	acrylic with lower adhesion		
Carrier	hard PE foam	orange	approx. 0,38
Adhesive open side	acrylic with higher adhesion		
Total thickness:			approx. 0,52

Product advantages

- The new adhesive system enables easy repositioning without lifting the tape from the cylinder.
- Reliable bond even during long and fast press runs (no plate lifting).
- Easy and clean demounting without residue on either plate or cylinder. No shellacking necessary.
- The flexible embossed film liner is designed for improved handling.

Main application fields

- Solids and line work
- Big letter
- No pinholing

Specific technical data*

Temperature range -20 °C to +70 °C

* Specific test results, statistically not approved.

DuploFLEX® 3.4

Art. No. 11 02 79

Compressible 0,38 mm (0.015") thick adhesive tape with distinctive orange colour for the mounting of plates in high-quality flexographic printing

Application

Recommended application temperature 18 °C to 35 °C

Application guidelines www.lohmann-tapes.com

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50 – 70%).
The storage stability is one year after delivery.

Product presentation

Converted product	Rolls				
Width [mm]	On request				
Length [m]	10/25				
Max. log width: 1260 mm					

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

The physical characteristics contained in our data sheets represent typical or average values. They do not represent any warranties or guarantees and must not be used for technical specification purposes. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. The buyer is responsible for determining the suitability of the specific tape for its intended use in connection with user's method of application. Please consult our Technical Applications Department for specific advice. Our general Term and Conditions of Sale apply, particularly with regard to warranty and liability.

Date of issue: March 2012

Lohmann GmbH & Co. KG

Irlicher Strasse 55

56567 Neuwied

Germany

Phone: + 49 (0) 26 31 34 - 0

Fax: + 49 (0) 26 31 34 - 6661

E-mail: info@lohmann-tapes.com

Für weitere Informationen

www.lohmann-tapes.com

Bei Anfragen bezüglich Produktsicherheit (Bestätigungen, Konformitäten mit Richtlinien, REACH, etc.) verwenden Sie bitte folgende E-Mail-Adresse: products.safety@lohmann-tapes.com

