

# DuploFLEX® 3115

Art. Nr. 11 230 C 00

**Single-sided film tape with a green PVC carrier and aggressive synthetic rubber adhesive**

## Product construction

	Name	Colour	Thickness [mm]
Adhesive	Synthetic rubber		approx. 0,057
Carrier	PVC film	green	
Total thickness:			approx. 0,057

## Product advantages

- High tear strength of PVC carrier.
- Excellent adhesive strength of the synthetic rubber on the relevant surfaces.
- DuploFLEX® 3115 is insured to humidity.
- Heat resistant up to +70°C.

## Main application fields

- Masking of cliché edges in the flexographic printing industry.

## Specific technical data\*

Temperature range	-20 °C to +70 °C
-------------------	------------------

\* Specific test results, statistically not approved.

# DuploFLEX® 3115

Art. Nr. 11 230 C 00

**Single-sided film tape with a green PVC carrier and aggressive synthetic rubber adhesive**

## Technical Data

<b>Peel strength</b>	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2 °C	5 N/25 mm
----------------------	---	-----------



## Application

**Recommended application temperature** 18 °C to 35 °C

**Application guidelines** [www.lohmann-tapes.com](http://www.lohmann-tapes.com)

## Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).

The storage stability is 6 months after delivery.

## Product presentation

Converted product	Rolls			Spools		
<b>Width [mm]</b>	25					
<b>Length [m]</b>	66					

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

The physical characteristics contained in our data sheets represent typical or average values. They do not represent any warranties or guarantees and must not be used for technical specification purposes. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. The buyer is responsible for determining the suitability of the specific tape for its intended use in connection with user's method of application. Please consult our Technical Applications Department for specific advice. Our general Term and Conditions of Sale apply, particularly with regard to warranty and liability.

Date of issue: December 2011

Lohmann GmbH & Co. KG

Irlicher Strasse 55

56567 Neuwied

Germany

Phone: + 49 (0) 26 31 34 - 0

Fax: + 49 (0) 26 31 34 - 6661

E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further Information

[www.lohmann-tapes.com](http://www.lohmann-tapes.com)

Concerning product safety (confirmation, conformity to guidelines, REACH, etc.) please use the following  
E-mail address: [products.safety@lohmann-tapes.com](mailto:products.safety@lohmann-tapes.com)

