

DuploFLEX® 5.2 Plus

Art. No. 11 00 02

Compressible 0.55 mm (0.020") thick foam tape with distinctive magenta colour for the mounting of plates in high-quality flexographic printing

Product construction			
	Name	Colour	Thickness [mm]
Liner	embossed PP-film	white	approx. 0,13
Adhesive covered side	Acrylic with lower adhesion		
Carrier	medium-soft PE-foam	magenta on the plate side	approx. 0,55
Adhesive open side	Acrylic with higher adhesion		
Total thickness:			approx. 0,68

Product advantages

- The hardness of the foam is clearly indicated by the colour coding system used.
- The new adhesive system enables easy repositioning without lifting the tape from the cylinder.
- Easy and clean demounting without residue on either plate or cylinder.
- No shellacking necessary.
- The flexible embossed film liner is designed for improved handling and virtually bubble-free mounting.
- The adhesion of DuploFLEX®Plus is increased approx. 20 % on both sides in comparison to DuploFLEX® range

Main application fields

- Process work
- Halftone reproduction
- Fine line graphics

Specific technical data*

Temperature range -20 °C to +90 °C

* Specific test results, statistically not approved.

DuploFLEX® 5.2 Plus

Art. No. 11 00 02

Compressible 0.55 mm (0.020") thick foam tape with distinctive magenta colour for the mounting of plates in high-quality flexographic printing

Application

Recommended application temperature	18 °C to 35 °C
Application guidelines	www.lohmann-tapes.com

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).
The storage stability is one year after delivery.

Product presentation

Converted product	Rolls	
Width [mm]	300	457
Length [m]	10/210/255	
Max. log width: 1060 mm	Other dimensions on request.	

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

The physical characteristics contained in our data sheets represent typical or average values. They do not represent any warranties or guarantees and must not be used for technical specification purposes. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. The buyer is responsible for determining the suitability of the specific tape for its intended use in connection with user's method of application. Please consult our Technical Applications Department for specific advice. Our general Term and Conditions of Sale apply, particularly with regard to warranty and liability.

Date of issue: February 2011

Lohmann GmbH & Co. KG
Irlicher Strasse 55
56567 Neuwied
Germany
Phone: + 49 (0) 26 31 34 - 0
Fax: + 49 (0) 26 31 34 - 6661
E-mail: info@lohmann-tapes.com

For further Information
www.lohmann-tapes.com



Concerning product safety (confirmation, conformity to guidelines, REACH, etc.) please use the following
E-mail address: products.safety@lohmann-tapes.com