

# DuploFLEX® FOL 0.10

Art. No. 11 00 15

**Double-sided plate mounting tape for letterpress and flexographic printing with filmic carrier and rubber adhesive**

Product construction			
	Name	Colour	Thickness [mm]
Liner	creped PVC film	green	approx. 0,70
Adhesive covered side	Rubber		
Carrier	PVC film	transparent	approx. 0,11
Adhesive open side	Rubber		
Total thickness:			approx. 0,81

## Product advantages

- The dimensional stable PVC film carrier in combination with an aggressive synthetic rubber pressure sensitive adhesive is particularly suitable for hard, tolerance-free mounting of printing plates in flexographic printing.
- Excellent tolerance compliance
- The adhesive system has been developed for the mounting of photo-polymer plates.
- The wide product range of DuploFLEX® has proved successful for more than 30 years.
- The thickness within the range is recognizable by the different coloured film carriers.

## Main application fields

- Mounting of photo-polymer plates on printing cylinders and mounting foils in flexographic and label printing

## Specific technical data\*

**Temperature range** -20 °C to +60°C

\* Specific test results, statistically not approved.


# DuploFLEX® FOL 0.10

Art. No. 11 00 15

**Double-sided plate mounting tape for letterpress and flexographic printing with filmic carrier and rubber adhesive**

## Technical Data

<b>Shear strength</b>	on steel according to DIN EN 1943, edition 1996, at +23 °C +/- 2 °C	60 N/625 mm <sup>2</sup>
<b>Peel strength</b>	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2 °C	20 N/25 mm



## Application

<b>Recommended application temperature</b>	18 °C to 35 °C
<b>Application guidelines</b>	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

## Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).  
The storage stability is 6 month after delivery.

## Product presentation

<b>Converted product</b>	Rolls					
<b>Width [mm]</b>	310	310	620			
<b>Length [m]</b>	4,5	25	25			
<b>Max. log width: 1240 mm</b>	Other dimensions, die-cuts and sheets on request.					

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

The physical characteristics contained in our data sheets represent typical or average values. They do not represent any warranties or guarantees and must not be used for technical specification purposes. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. The buyer is responsible for determining the suitability of the specific tape for its intended use in connection with user's method of application. Please consult our Technical Applications Department for specific advice. Our general Term and Conditions of Sale apply, particularly with regard to warranty and liability.

Date of issue: December 2011

Lohmann GmbH & Co. KG  
Irlicher Strasse 55  
56567 Neuwied  
Germany  
Phone: + 49 (0) 26 31 34 - 0  
Fax: + 49 (0) 26 31 34 - 6661  
E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further Information  
[www.lohmann-tapes.com](http://www.lohmann-tapes.com)



Concerning product safety (confirmation, conformity to guidelines, REACH, etc.) please use the following  
E-mail address: [products.safety@lohmann-tapes.com](mailto:products.safety@lohmann-tapes.com)